

X SERIES

Perfect Wave Screen Solution

INFILED



- Faster and easier to build
- Separate control unit
- Allow for perfect smooth curves
- Flat panel and corner panel optional
- 2mm&3mm available

SPECIFICATIONS

Part Number	IL-RSS-IRX2	IL-RSS-IRX3
Pixel Pitch	2.9mm	3.9mm
Physical Density	112,896pixels/m ²	65,536pixels/m ²
LED Arrangement	3 IN 1 SMD	3 IN 1 SMD
Module Resolution	168×42pixels	128×32pixels
Module Dimension	500×125mm(19.69×4.92in)	500×125mm(19.69×4.92in)
Cabinet Resolution	168×168pixels	128×128pixels
Cabinet Dimension	500×500×84mm(19.69×19.69×3.31in)	500×500×84mm(19.69×19.69×3.31in)
Cabinet Weight	8.9kg(19.62lb)	8.9kg(19.62lb)
Brightness Level	≥ 1,200nits	≥ 1,200nits
Max Power Consumption	180w/panel	180w/panel
Ave Power Consumption	60w/panel	60w/panel
Viewing Angle	110°/110°	110°/110°
Operating Power Source	100-240V AC 50-60Hz	100-240V AC 50-60Hz
Operating Temperature	-10°C~+45°C	-10°C~+45°C
Refresh Rate	1,000~3,840Hz(Configurable)	1,000~4,800Hz(Configurable)
Protecting Rating	IP30	IP30
Signal Input Source	Composite, S-Video, Component, VGA, DVI, HDMI, SDI, HD SDI	Composite, S-Video, Component, VGA, DVI, HDMI, SDI, HD SDI
Verification	CE, EMC, LVD	CE, EMC, LVD

FOR SALES AND RENTAL

MATRIXVISUAL.COM 1.888.8MATRIX

1748 West Business Center Drive. Orange, California 92867

