




“
Single person handles all
Concave and convex curve
Hanging and stacking install
”

SPECIFICATIONS

Pixel Pitch	5.9mm	
Panel size	W500m×H500mm×D86mm	
Pixels per panel)	84×84 Dots	
Area	0.25 m ²	
Weight	20.28 lbs/panel	
Material	Die-casting Aluminum	
Pixel density	43264 pixels/m ²	
Brightness	5000 nits(black face)	5500 nits(black body)
Processing depth	16bits	
Gray scale	65536 levels per color	
Color	281.4 trillion	
Contrast ratio	5000:1(black face)	3000:1(black body)
Viewing angle	H: 140°; V:120°	
Recommended viewing distance	≥5.9 M	
Video frame rate	50/60Hz	
Rate refresh	3840Hz	
Supply power source	110~220VAC±15%	
Power consumption <max>	230W/panel	210W/panel
Power consumption <typical>	76W/panel	70W/panel
Ingress protection	IP65/ IP65	
Operating Temperature/Humidity	-20℃~+50℃/10~90% RH	
Storage Temperature/Humidity	-30℃~+60℃/10~90% RH	
Life Span	≥100,000 Hours	
Maintenance	Rear Access	
Rigging form	Hanging/Ground Stacking	

Specifications are subject to change without prior notice.