



“
**Single person handles all
 Concave and convex curve
 Hanging and stacking install**
 ”

SPECIFICATIONS

| | | |
|--------------------------------|-----------------------------|-----------------------|
| Pixel Pitch | 6.9mm | |
| Panel size | W500m×H500mm×D86mm | |
| Pixels per panel) | 72×72 Dots | |
| Area | 0.25 m ² | |
| Weight | 20.28 lbs/panel | |
| Material | Die-casting Aluminum | |
| Pixel density | 20736 pixels/m ² | |
| Brightness | 5000 nits(black face) | 5500 nits(black body) |
| Processing depth | 16bits | |
| Gray scale | 65536 levels per color | |
| Color | 281.4 trillion | |
| Contrast ratio | 5000:1(black face) | 3000:1(black body) |
| Viewing angle | H: 140°; V:120° | |
| Recommended viewing distance | ≥6.9 M | |
| Video frame rate | 50/60Hz | |
| Rate refresh | 3840Hz | |
| Supply power source | 110~220VAC±15% | |
| Power consumption <max> | 230W/panel | 210W/panel |
| Power consumption <typical> | 76W/panel | 70W/panel |
| Ingress protection | IP65/ IP65 | |
| Operating Temperature/Humidity | -20℃~+50℃/10~90% RH | |
| Storage Temperature/Humidity | -30℃~+60℃/10~90% RH | |
| Life Span | ≥100,000 Hours | |
| Maintenance | Rear Access | |
| Rigging form | Hanging/Ground Stacking | |

Specifications are subject to change without prior notice.